Form PTO 1449 (Modified)		U.S. DEPARTMEN	T OF COMMERCE ADEMARK OFFICE	ATTY DOCKET NO.		SERIAL NO.			
(woomea)		TATEM AND TO	OEMPH (COLINE	261524US3PCT	10/512,083				
				APPLICANT					
LISTOF	KEFE	RENCES CITED BY A	PPLICANT	Yoshihisa OKUNO					
				FILING DATE		GROUP			
				January 10, 2006	3618				
				U.S. PATENT DOCUMENTS					
EXAMINER INITIAL		DOCUMENT NUMBER	DATE	NAME	CLASS	SUB CLASS	FILING DATE IF APPROPRIATE		
	AA								
	AB								
	AC								
	AD								
	AE								
	AF								
	AG								
	AH								
	Al								
	AJ								
	AK		-				***************************************		
	AL								
	AM								
	AN								
FOREIGN PATENT DOCUMENTS									
		DOCUMENT NUMBER	DATE	COUNTRY	TRANSLATION YES NO				
	AO	JP 58-43516	03/23/1983	Japan				X	
	AP								
	AQ								
	AR								
	AS								
	AT								
	AU								
	AV								
OTHER REFERENCES (Including Author, Title, Date, Pertinent Pages, etc.)									
	AW								
	AX							,	
	AY								
	AZ				Addi	Additional References sheet(s) attached			
Examiner		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,			Date Considered				
*Examiner: Init conformance a	tial if re	eference is considered, t considered. Include co	whether or not opy of this form	citation is in conformance with MPEP 6 with next communication to applicant.	09; Draw lir	ne through	citation	if not in	

H:\26S\261524US (BDL)\261524US 1449 8.6.07.DOC

DOCKET NO.: 261524US3PCT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

IN RE APPLICATION OF:

Yoshihisa OKUNO

SERIAL NO: 10/512,083 GROUP: 3618

FILED: January 10, 2006 EXAMINER: SWENSON, B.

FOR: RADIATOR DEVICE FOR TWO-WHEELED MOTOR VEHICLE

STATEMENT OF RELEVANCY

Reference AO on Form 1449:

This discloses a radiator mounting structure of a motorcycle in which a water-cooled V-type engine is mounted to a frame body in a manner inclined in a longitudinal direction of the vehicle body, and a radiator for cooling a cooling water of the engine is arranged between a front wheel and a downtube forming the frame body. In such motorcycle, an upper end portion of the radiator is mounted to the frame body through a hinge so that the radiator is rotatable in the longitudinal direction of the vehicle body with the hinge being a fulcrum.